


# LED PAR38

3000 Lumen 27 Watt 4000K  
PAR38 - 25° 120-277V



## PRODUCT DESCRIPTION


27 watt PAR38 EarthBulb LED floodlight replaces 250 watt incandescent floodlights for over 85% energy savings. This PAR38 combines high lumen output and energy efficiency. High power LED and an advanced cooling system provides for 40,000 hours of LED life. Medium screw base. Wet location rated. Dimmable when used on 120VAC.

## PRODUCT FEATURES

- Dimming when used on 120VAC
- PAR38 flood light provides 3000 lumens
- 25° beam angle provides a flood, not spot light
- Unique LED array design look like halogen when powered on
- Super Bright – 2x brighter
- Wet rated UL and suitable for exterior locations
- Fits track heads like a PAR lamp is intended

## PRODUCT APPLICATIONS

- Architectural Track Lighting
- Recessed & Decorative Lighting
- High-End Residential & Office Environments
- Mezzanines
- House of Worship
- Specialty Retail Shops



**MODEL NUMBER: LP38274025HO**  
**ORDER CODE: 11271**

| Order Code                                    | Individual UPC     | Master Park UPC      | Qty |
|---|--------------------|----------------------|-----|
| 11271   | 840791112717       | 840791112717000      | 6   |
| Dimensions (inches - Length x Width x Height) |                    |                      |     |
| 11271   | 4.92 x 4.92 x 5.64 | 15.63 x 10.52 x 6.69 | 6   |
| Weight (lbs)                                  |                    |                      |     |
| 11271   | .664               | 9.856                | 6   |

| Electrical                  |              |
|-----------------------------|--------------|
| Watt                        | 27           |
| Power Factor                | > 0.9        |
| Voltage                     | 120-277 volt |
| Frequency                   | 60Hz         |
| Base Type                   | E26 Medium   |
| Operating Temperature Range | -4F to 104F  |
| Light                       |              |
| Initial Lumens              | 3000         |
| Lumens per Watt             | 111          |
| Color Temperature           | 4000K        |
| Color Rendering (CRI)       | 80+          |
| Beam Angle                  | 25°          |
| Agency Approvals            |              |
| UL                          | Yes          |
| Rated Hours                 | 40,000 hours |
| RoHS                        | Yes          |
| FCC                         | Yes          |
| Product Details             |              |
| Warranty                    | 5 years      |
| Diameter                    | 4.72"        |
| Nominal Length              | 5.12"        |