# LED PAR38



Electrical		
Watt	27	
Power Factor	> 0.9	
Voltage	120-277 volt	
Frequency	60Hz	
Base Type	E26 Medium	
Operating Temperature Range	-4F to 104F	
Light		
Initial Lumens	3000	
Lumens per Watt	111	
Color Temperature	5000K	
Color Rendering (CRI)	80+	
Beam Angle	25°	
Agency Approvals		
UL	Yes	
Rated Hours	40,000 hours	
RoHS	Yes	
FCC	Yes	
Product Details		
Warranty	5 years	
Diameter	4.72"	
Nominal Length	5.12"	

## 3000 Lumen 27 Watt 5000K PAR38 - 25° 120-277V



#### PRODUCT DESCRIPTION

27 watt PAR38 EarthBulb LED floodlight replaces 250 watt incandescent floodlights for over 85% energy savings. This PAR38 combines high lumen output and energy efficiency. High power LED and an advanced cooling system provides for 40,000 hours of LED life. Medium screw base. Wet location rated. Dimmable when used on 120VAC.

### PRODUCT FEATURES

- Dimming when used on 120VAC
- PAR38 flood light provides 3000 lumens
- 25° beam angle provides a flood, not spot light
- Unique LED array design look like halogen when powered on
- Super Bright 2x brighter
- · Wet rated UL and suitable for exterior locations
- · Fits track heads like a PAR lamp is intended

#### PRODUCT APPLICATIONS

- · Architectural Track Lighting
- · Recessed & Decorative Lighting
- · High-End Residential & Office Environments
- Mezzanines
- · House of Worship
- · Specialty Retail Shops







MODEL NUMBER: LP38275025HO

**ORDER CODE: 11272** 

Order Code	Individual UPC	Master Park UPC	Qty
11272	840791112704	84079111272400	6
Dimensions (inches - Length x Width x Height)			
11272	4.92 x 4.92 x 5.64	15.63 x 10.52 x 6.69	6
Weight (lbs)			
11272	.664	9.856	6

